



ELECTRONIC DIGITAL LEVEL

# DL-101C/102C



## MAIN FEATURES

### Faster Automatic Measurement

When used with TOPCON's unique patterned staff, height and distance can be automatically determined digitally by the DL-101C/102C.

Since it's a fully automatic electronic measurement, there is no need to make an optical reading! You just sight the staff, focus, and press the measurement button. It's that simple! The results appear in the clearly visible display window after about three seconds.

### Highly Accurate Measurements

The fully automatic measuring ability and digital display of the DL-101C/102C excludes any reading errors, writing mistakes in the field book, and other possible human-made errors. Consequently, the electronic measurement data is always more precise and more reliable as compared to the conventional visual measurement.



### Increased Productivity up to 50%

With TOPCON's DL-101C/102C, all leveling work can be carried out automatically, quickly and more economically as compared to the performance of conventional optomechanical levels. This effortless and error-free measurement makes it possible to have up to a 50% increase in productivity.

### PCMCIA Memory Card System

The PCMCIA world standard memory card system can be used with DL-101C/102C. Memory cards up to 2MB are available for memory storage in addition to the instrument's internal memory capacity of 256KB. The internal memory can store up to 8,000 levelled points. The PCMCIA memory card slot is concealed behind the battery compartment. This ensures watertight protection of the PCMCIA card. Data recording directly to either internal memory or PCMCIA card is selectable.



### Screen Backlight

The display screen has a software controlled backlight that can be set on or off and brightness control at 9 levels to ensure easy viewing of the screen in bright, shadow and dark conditions.

### 5m staff

Levelling staffs of a variety of materials and length are available with the special Topcon pattern to allow Digital Measurements with DL-101C/102C.

### Data Output Function

Standard RS-232C port provides an instant communications link with a data collector or direct output to a personal computer.

# SPECIFICATIONS

	DL-101C	DL-102C
<b>TELESCOPE</b>		
Magnification	32×	30×
Objective Aperture	45mm	
Field of view	1°20'	
Resolving power	3"	
<b>COMPENSATOR</b>		
Working Range	±12'	±15'
Setting Accuracy	±0.3"	±0.5"
<b>HEIGHT MEASUREMENT</b>		
Accuracy (Standard deviation for 1km double-run levelling)		
Electronic reading	0.4mm w/Invar staff	1.0mm w/Fiberglass staff
Optical reading	1.0mm	1.5mm
Least Count	0.1mm/0.01mm (0.001ft/0.0001ft)	1mm/0.1mm (0.01ft/0.001ft)
<b>DISTANCE MEASUREMENT</b>		
Least Count	1cm/1mm	1cm
Accuracy	1cm to 5cm	
<b>MEASURING RANGE</b>	2m to 100m (7ft to 328ft): Fiberglass staff/Aluminum staff 2m to 60m (7ft to 197ft): Invar staff	
<b>MEASURING TIME</b>	3 sec.	
<b>CIRCULAR LEVEL SENSITIVITY</b>	8'/2mm	10'/2mm
<b>OTHERS</b>		
Display	2-line, 8-digit per line. Dot matrix LCD with backlight	
Data Storage	PCMCIA card (64KB to 2MB) Internal memory approx. 8,000 data	
Data Transmission	RS-232C port provided	
Keyboard	Alphanumeric input	
Timer	Built-in timer	
Horizontal Circle	360° or 400gon	
Power Supply	AA size dry cell batteries × 6 [Option: Rechargeable Battery BT-31Q]	
Operating Time	10 hours (Dry cell – Alkaline) [10 hours (BT-31Q Rechargeable Battery)]	
Ambient Temperature Range	-20°C to +50°C [-4°F to +122°F]	
Dimensions	237 × 196 × 141mm [9.33 × 7.72 × 5.55 inch]	
Weight	2.8 kg [6.16 lbs] (including on-board battery)	
Data Card	PC card based on PCMCIA (SRAM: 64K~2M byte)	
<b>STAFF</b>		
Aluminum staff SA-5M	Length: 5.0m [16.40ft] (Slide Type: 3 pcs.)	
Fiberglass staff SG-3M	Length: 3.0m [9.84ft] (1.5m [4.92ft] × 2 pcs.) Graduation: 1cm graduation with 5mm pattern (front surface)	
Invar staff SI-3/T or SI-3	Length: 3.0m [9.84ft]	

• Designs and specifications herein are subject to change without notice.

**Important** In order to obtain the best results with this instrument, please be sure to review all user instructions prior to operation.

# STANDARD SET COMPONENTS



- Instrument DL-101C or DL-102C (with lens cap).....1 pc.
- Carrying case.....1 pc.
- Plastic rain cover.....1 pc.
- Silicon cloth.....1 pc.
- Plumb bob set.....1 set
- Adjusting pin.....1 pc.
- Instruction manual.....1 vol.
- Dry battery holder DB-31.....1 pc.
- AA size dry cell batteries.....6 pcs
- OPTION**
- Rechargeable Battery BT-31Q
- Battery charger BC-23B or BC-23C.....1 pc.  
(AC120V) (AC230V)



Certificate No. Q/3102  
**TOPCON CORPORATION**  
 Surveying Instruments Division (Tokyo)



75-1 Hasunuma-cho, Itabashi-ku, Tokyo 174-8580, Japan Phone: 3-3558-2520 Fax: 3-3960-4214 www.topcon.co.jp

## TOPCON AMERICA CORPORATION

CORPORATE OFFICE  
 37 West Century Road, Paramus, New Jersey 07652, U.S.A  
 Phone: 201-261-9450 Fax: 201-387-2710 www.topcon.com

TOPCON CALIFORNIA  
 3380 Industrial Blvd., Suite 105, West Sacramento, CA 95691, U.S.A  
 Phone: 916-374-8575 Fax: 916-374-8329

TOPCON MIDWEST  
 891 Busse Road, Elk Grove Village, IL 60007, U.S.A  
 Phone: 847-734-1700 Fax: 847-734-1712

TOPCON LASER SYSTEMS, INC.  
 5758 West Las Positas Blvd., Pleasanton, CA 94588, U.S.A  
 Phone: 925-460-1300 Fax: 925-460-1315 www.topconlaser.com

TOPCON EUROPE B.V.  
 Esse Baan 11, 2908 LJ Capelle a/d IJssel, The Netherlands  
 Phone: 010-4585077 Fax: 010-4585045 www.topconeuropa.com

TOPCON BELGIUM  
 Preenakker 8, 1785 Merchtem, Belgium  
 Phone: 052-37 45 48 Fax: 052-37 45 79

TOPCON DEUTSCHLAND G.m.b.H.  
 Halskestr. 7, 47877 Willich, Germany  
 Phone: 02154-9290 Fax: 02154-9291-111 Telex: 8531981 TOPC D

## TOPCON S.A.R.L.

89, Rue de Paris, 92585 Clichy, Cedex, France  
 Phone: 33-1-41069490 Fax: 33-1-47390251 topcon@topcon.fr

## TOPCON ESPAÑA S.A.

HEAD OFFICE  
 Frederic Mompou 5, 08960, Sant Just Desvern Barcelona, Spain  
 Phone: 93-473-4057 Fax: 93-473-3932

MADRID OFFICE  
 Avenida Burgos, 16E, 1° 28036, Madrid, Spain  
 Phone: 91-302-4129 Fax: 91-383-3890

## TOPCON SCANDINAVIA A. B.

Industrivägen 4 P. O. Box 2140 43302 Sävedalen Sweden  
 Phone: 031-261250 Fax: 031-268607 Telex: 21414

## TOPCON (GREAT BRITAIN) LTD.

HEAD OFFICE  
 Topcon House Kennet Side, Bone Lane, Newbury, Berkshire RG14 5PX U.K.  
 Phone: 44-1635-551120 Fax: 44-1635-551170  
 survey.sales@topcon.co.uk laser.sales@topcon.co.uk

## TOPCON SINGAPORE PTE. LTD.

Alexandra Distripark Block 4, #05-15, Pasir Panjang Road, Singapore 118491  
 Phone: 2780222 Fax: 2733540 E-mail: topcon@smgnet.com.sg

## TOPCON AUSTRALIA PTY. LTD.

408 Victoria Road, Gladstone, NSW 2111, Australia  
 Phone: 02-9817-4666 Fax: 02-9817-4654

## TOPCON INSTRUMENTS (THAILAND) CO., LTD.

77/162 Sinn Sathorn Tower, 37th Fl.  
 Krungthornburd Rd., Klonglonsai, Klongsarn, Bangkok 10600 Thailand  
 Phone: 662-440-1152-7 Fax: 662-440-1158

## TOPCON INSTRUMENTS (MALAYSIA) SDN. BHD.

Lot 226 Jalan Negara 2, Pusat Bandar Taman Melawati,  
 Taman Melawati, 53100, Kuala Lumpur, Malaysia  
 Phone: 03-4079801 Fax: 03-4079796

## TOPCON KOREA CORPORATION

Hyobong Bldg., 1306-1, Seocho-Dong, Seocho-Gu, Seoul, Korea  
 Phone: 02-3482-9231 Fax: 02-3481-1928

## TOPCON OPTICAL (H.K.) LIMITED

2/F, Meeco Industrial Bldg., No. 53-55 Au Pui Wan Street, Fo Tan Road,  
 Shatin, N.T., Hong Kong  
 Phone: 2690-1328 Fax: 2690-2221 www.topcon.com.hk

## TOPCON CORPORATION BEIJING OFFICE

Room No. 962 Poly Plaza Building, 14 Dongzhimen Nandajie,  
 Dongcheng District, Beijing, 100027, China  
 Phone: 10-6501-4191-2 Fax: 10-6501-4190

## TOPCON CORPORATION BEIRUT OFFICE

P. O. BOX 70-1002 Arietias, BEIRUT-LEBANON  
 Phone: 961-4-523525/961-4-523526 Fax: 961-4-521119

## TOPCON CORPORATION DUBAI OFFICE

Office No. 102, Khailal Rashid Al Nayli Bldg., 245 Abu Hail Road, Dera Dubai, UAE  
 Phone: 971-4-2696511 Fax: 971-4-2695272